



TABLE OF QUANTITIES

"W" FEET	POLYETHYLENE SHEET SQ. FT.	CONNECTING BAND INCHES (MIN.)	STAINLESS STEEL CLAMPS	NUMBER OF 1/4" x 1" BOLTS
4	17	6	2	6
5	26.3	8	2	6
6	37.5	8	2	6
		8	2	6

NUMBER OF ANTISEEP COLLARS REQUIRED = _____

NOTES:

1. THE PIPE, CONNECTING BAND, AND SEAM COATING CAN BE EITHER SILICON CAULKING (RECOMMENDED), TAR OR MASTIC.
2. APPLY SILICON CAULK, TAR, OR MASTIC TO THE CONNECTING BAND AND LAY THE PIPE ON IT. APPLY SILICON CAULK, TAR, OR MASTIC TO THE OTHER HALF OF THE CONNECTING BAND AND SET IT IN PLACE, LINING UP THE BOLT HOLES.
3. INSTALL THE STAINLESS STEEL CLAMPS ON THE SPLIT HALVES OF THE CONNECTING BANDS AND TIGHTEN THE BOLTS AND CLAMPS.
4. APPLY SILICON CAULK, TAR, OR MASTIC ON THE SEAMS AS NEEDED TO INSURE A GOOD SEAL SO THAT THE COMPLETED INSTALLATION IS WATERTIGHT.



United States
Department of
Agriculture

Natural Resources
Conservation Service

POLYETHYLENE ANTISEEP COLLAR
FOR 4" DIAMETER PIPE

CLIENT: _____
COUNTY: _____

Designed _____ Date _____
Drawn _____
Checked _____
Approved _____

File Name
WI-246
Date
07/14
Sheet of _____