



TRIANGULAR  
GROOVE

DIMENSIONS

- Dia = \_\_\_\_\_ (in)  
 A = \_\_\_\_\_ (in)  
 B = \_\_\_\_\_ (in)  
 C = \_\_\_\_\_ (in)  
 D = \_\_\_\_\_ (in)  
 W = \_\_\_\_\_ (in)

ROCK GRADATION

- D<sub>100</sub> = \_\_\_\_\_ min (in) \_\_\_\_\_ max (in)  
 D<sub>75</sub> = \_\_\_\_\_ min (in) \_\_\_\_\_ max (in)  
 D<sub>50</sub> = \_\_\_\_\_ min (in) \_\_\_\_\_ max (in)  
 D<sub>min</sub> = \_\_\_\_\_ min (in) \_\_\_\_\_ max (in)

NOTE:  
 This standard drawing requires supporting technical documentation prior to use and must be adapted to the specific site.

Drawing not to scale.

|  |                              |                |                |
|--|------------------------------|----------------|----------------|
|  | JOB CLASS                    |                | Date           |
|  | CAD FILE NO.<br>DRN-0002.DWG | Designed _____ | _____          |
|  | SHEET OF                     | Drawn _____    | _____          |
|  |                              | Checked _____  | _____          |
| <b>U.S.D.A. NATURAL RESOURCES CONSERVATION SERVICE</b> |                              |                | Approved _____ |